



Cat. #	Type
Notes	

APPLICATIONS

- The RQ LED light is a high performance dot light ideally suited for direct-view application such as large-scale video at building facade, graphics, architectural and decorative lighting applications. It is easy-to-install and has two sizes for different applications.

SPECIFICATIONS

- Use Nichia Japan high brightness SMD LEDs with 50,000 hours operation life time. There is different choice of colors including red, green, blue, amber, cool white, warm white and RGB.
- The dot light has 150° beam angle. It is DMX512 controlled for RGB and mono color version with built-in driver.
- The housing is made of die-cast aluminum with anti-UV foggy polycarbonate lens. It is filled up with UV-stabilized silicon gel with IP66 protection rating for outdoor installation. The operating temperature range is 0-50°C.
- There are two versions of DS-RQ, one is 2-3/8" diameter with power consumption of 2.5W and the other is 3" diameter with power consumption of 3W. They are both operated at 21 ~ 26VDC voltage.

INSTALLATION

- Surface mount by screwing the dot light directly onto mounting surface.

RQ LED Dot Light

DS-RQ



DIMENSIONS		
All dimensions are shown in inches (mm)		
Diameter	Depth	Power Consumption
2-3/8"(61)	1-1/2"(39)	2.5W
3"(75)	1-3/4"(45)	3W

ORDERING INFORMATION

Series	Color	Diameter	Beam Angle	Voltage	Connector	Tail Cable
DS-RQ	RGB	2-3/8"(61)	120°	24VDC	JWPF	8"
	Red	3"(75)				
	Green					
	Blue					
	Amber					
	Cool White					
	Warm White					

Notes

- The color of LED is selectable.
- Listing - CSA certified to US and Canadian standards.
- The input voltage is 24VDC.
- Longer tail cable length than 8" must be specified when ordering.
- JWPF connector is standard. If client wants bare cable out, it must be specified.



DS-RQ

Accessories Ordering

C2000	DMX controller with 1024 DMX address	AC-004	Milky white polycarbonate lens for DS-RQ-8
C4000	DMX controller with 2048 DMX address	AC-005	Milky white polycarbonate lens for DS-RQ-12
ICS8000	DMX controller with 4096-262144 DMX address	EC11	Extension cable (2m)
CLG-150-24	150W power supply unit		
HLG-240H-24	240W power supply unit		

Notes

1. Please specify length of extension cables if longer than 2m



Milky White Polycarbonate Lens for DS-RQ-08
Model : **AC-004**




Milky White Polycarbonate Lens for DS-RQ-12
Model : **AC-005**



Extension Cable
Model : **EC11 (2m long)**

TECHNICAL DRAWING

(All dimensions are shown in mm)



MOUNTING

(All dimensions are shown in mm)

